

MBS-PRO

All-in-1 Pro Sensor (Temp/Humid/CO2/Light)

The MBS-PRO 4-in-1 sensor combines a precision air temperature, humidity, CO2 and photocell sensor to create the perfect 4-in-one environmental sensor. It is designed for Hydro-X Pro and Hydro-X Plus.

Assembled using a water-resistant plastic injection enclosure and “push-lock” connection to make installation easy. The MBS-PRO can be placed in multiple locations throughout the growing area to provide spot measurements from multiple sensors. (Up to 50 sensors can be connected to the Hydro-X Pro)

The sensors can then be used together (averaged) or separately in order to control a specific section of the grow area by assigning a sensor to a specific control device.

The MBS-PRO built-in LCD display also functions as an on-site sensor display monitor.

***Note:** The MBS-Pro requires the SPH-1 for supplemental power.

***Note:** Sensors should remain dry and clean to prevent premature failure. Do not spray foreign substances or allow water / condensate on the sensors.



Specifications

MBS-PRO

Input Voltage

Voltage	12VDC
---------	-------

Maximum Current

Current	0.04A
---------	-------

Working Environments

Temperature	32-122°F (0-50°C)
-------------	-------------------

Humidity	5-95%RH
----------	---------

Package Content

MBS-PRO Sensor	1pc
----------------	-----

16ft RJ12 Cable	1pc
-----------------	-----

T-Shape Splitter	1pc
------------------	-----

Package Dimensions

Size	10.83inch / 275mm(L) x 6.46inch / 164mm(W) x 2.56inch / 65mm(H)
------	---

Gross Weight	1.17lbs / 0.53kgs
--------------	-------------------

Range And Accuracy

Temperature Range	32-138.2°F
-------------------	------------

Temperature Accuracy	±0.36°F
----------------------	---------

Humidity Range	5-90%
----------------	-------

Humidity Accuracy	±3%
-------------------	-----

CO2 Range	0-5000PPM
-----------	-----------

CO2 Accuracy	±30ppm ±5% of reading
--------------	-----------------------

Link Up

MBS-PRO

CONNECTION DIAGRAM

